

inORéa

Automatismes & Industrie






TECHNICAL SPECIFICATIONS SHEET



COMPOUND ROTARY BUTTONS

Inoréa Automation & Industry
9 rue du Lugan
33130 Bègles, FRANCE
contact@inorea.com
www.inorea.com

1. Standards compound rotary buttons

Photos	Composition	Features	References	Diagram
	Power button, normally open contact block, button support, label holder and marking label	<ul style="list-style-type: none"> - 2 positions: maintained 60° / Black - 2 positions: return to center/ Black + 1 contact NO 	<ul style="list-style-type: none"> - BPC_R2P_1NO - BPC_R2R_1NO 	 
	Power button, 2 normally open contact blocks, button support, label holder and marking label	<ul style="list-style-type: none"> - 3 positions: maintained 60° / Black + 2 contacts NO - 3 positions: return to center 60° / Black + 2 contacts NO 	<ul style="list-style-type: none"> - BPC_R3P_2NO - BPC_R3R_2NO 	 
	Long lever electric button, 2 blocks from normally open contact, support button support label and marking label	<ul style="list-style-type: none"> - 3 positions return to center 60° with long lever button / Noir + 2 contacts NO 	<ul style="list-style-type: none"> - BPC_RBS_2NO 	
	Electric lever button, normally open contact block, support button, support label and marking label	<ul style="list-style-type: none"> - ON/OFF: lever button / 1 contact NO 	<ul style="list-style-type: none"> - BPC_TOG_1NO 	<p>O - I</p>

2. Bright compound rotary buttons

Photo	Composition	Features	References	Diagram
	Bright button, normally open contact block, LED 24V AC / DC 17 mA White LED, LED support, button support, label support and marking label.	2 positions: maintained 60° 24V / transparent + 1 contact NO	BPC_LRM_1NO_024	
	Bright button, normally open contact block, White LED 230 V AC, LED support, button support, label support and marking label..	2 positions: maintained 60° 230V / transparent + 1 contact NO	BPC_LRM_1NO_230	
	Bright button, normally open contact block, LED 24V AC / DC 17 mA White LED, LED support, button support, label support and marking label.	3 positions: maintained 60° 24V / transparent + 2 contacts NO	BPC_LRM_2NO_024	
	Bright button, normally open contact block, White LED 230 V AC, LED support, button support, label support and marking label.	3 positions: maintained 60° 230V / transparent + 2 contacts NO	BPC_LRM_2NO_230	